

HiVol 3000

HIGH VOLUME AIR SAMPLER



The HiVol 3000 particulate sampler performs remote unattended sampling of PM_{2.5}, PM₁₀ or TSP along with basic meteorological parameters.

The HiVol 3000 incorporates advanced programming functions and electronic volumetric flow control to maintain a consistent flow and collect a truly representative sample of particulate matter.

Optional attachments allow the sampler to measure wind speed and direction which can then be used to trigger sector selectable sampling (e.g. fence-line monitoring).

APPROVALS

- US EPA Manual Reference Method: RFPS-0706-162 approval for PM₁₀
- Meets Australian standard for PM₁₀ and TSP monitoring
- Only high volume air sampler with CE and C-tick approval
- Manufactured under ISO9001.

RELIABLE SAMPLING

- Volumetric flow control automatically corrected to standard reference temperature
- Programmable reference temperatures
- Industrial brushless motor (100,000 hours continuous field operation)
- Weather-proof marine quality anodised aluminium cabinet
- Automatic supply voltage monitoring and shut-down facility reduces damage to instrument.

DIRECTIONAL SAMPLING

- Wind direction and speed used to activate/de-activate sampler
- External trigger (0 - 5 VDC) can be used for activating sampling program.

ENHANCED COMMUNICATION

- RS232 output for data collection and remote communication
- Filter blocked and instrument error alarms
- Total control of instrument remotely from PC
- Simple programming of sampling periods, including daily and weekly programs, with in-built "1-in-X day" sampling capability.

SPECIFICATIONS

Operation:	Microprocessor controlled (internal data logging)
Pump/Motor:	Side channel blower driven by an induction motor (brushless)
Flow controller:	Variable frequency drive
Volumetric flow range:	Nominal 45 - 96 m ³ /hr
Vacuum capability:	140 mBar max
Flow accuracy:	Better than ± 1 m ³ /hr
Flow repeatability:	± 1 % of reading
Construction:	Anodised aluminium and stainless steel fasteners
Filter size:	250 x 200 mm rectangular element
Dimensions:	380 x 380 x 1200 mm plus inlet
Weight:	45 kg plus inlet weight
Operating voltage:	200 - 240 V + 10 % 50/60 Hz (optional 115 V 60 Hz)
Power Consumption:	1500 VA Max (depending on filter loading & flow rate)
Temp measurement range:	0 - 50 °C
Barometric pressure:	600 - 900 mmHg \pm 4 mmHg

COMMUNICATION & DATA LOGGING

No. of readings

- 150 (user selectable averaging period,
e.g. 75 hrs of 30 min averages)

External inputs

- 1 x wind direction sensor input (10k potentiometer)
- 1 x wind speed sensor input (contact closure)
- 1 x spare contact closure input (e.g. tipping bucket rain gauge).

Output

- RS232C

OPTIONS

- PM₁₀, PM_{2.5} or TSP size selective inlets
- Calibration plate and field calibration transport case
- Manometer
- WS/WD sensors
- RH Sensor
- Muffler.



AMERICAN ECOTECH
100 Elm Street, Factory D, Warren, RI 02885
(877) 247-0403 info@americanecotech.com www.americanecotech.com

Specifications subject to change without notice. Ecotech & HVOI are trademarks or registered trademarks of ECOTECH Pty Ltd in the United States and/or other countries. © 2017 ECOTECH Pty Ltd. All rights reserved. 20171129

 AMERICAN
ECOTECH
Air Pollution Monitoring Systems